




Model: PERGO-Y

Turn Your Living Inside Out with the Perfect Addition to your Outdoor Living Space





Create a luxurious, relaxing and entertaining space with our innovative aluminium Louvered Roof - Alucit Pergo-Y, available in a range of sizes.



Alucit Pergo-Y Features

- Power-coated AkzoNobel aluminium with 5-years-warranty for outdoor discolouration
- Flat-ceiling Louver Blade with anti-sagging design for waterproofness
- Gutter incorporated with beam and single-sided control rod for quick assembly
- Each post comes with die-casting base cover to keep the base plate/anchor bolts invisible
- The post surface is flushed/smooth all the way up to the gutter top
- RGB LED Lighting around guttering could be optional for this model









Blade 158x 33 x 1.3mm

Motor 168 x 85 x 1.8mm



Post 120 x 120 x 1.8mm




Gutter 175 x 93 x 1.5mm






Motorized System














Louvers are designed such that they will interlock to keep out the water, hot sun and snow. Deep channels in each louvers carry water away to the in-built surrounding gutter.

Tilt the louvers like that, the sun is blocked and the fresh air can flush through the opening gaps.

With 100° opening angle, you can still enjoy the sunshine and sunset. In the event of rain, our pergola is closed to provide complete protection. Water is channeled away directly through the internal drain hidden inside the post.





Optional Sizes



• 2.929 x 2.929m

2.929 x 5.672m



Optional Colors



















Liner Strip LED Lights



Motorized Side Screen



Aluminium Fencing





Product Picture	Produc t Size (m)	Packing Information (mm) /set						Remark
		CTN NO. L	W H G.V	V CBM				Kelliark
	2.863x2.863x2.5m	1/4	2864	315	23	40.17	0.21	Gutter + Blade
		2/4	2861	351	6	43.97	3	Blade
		3/4	2861	351	23	40.05	0.23	Blade
		4/4	2774	274	3	52.04	4	Post + Accessories Box
	2.863x4.000x2.5m	1/4	4001	315	23	48.47	0.23	Gutter + Blade
		2/4	2861	351	3	61.11	4	Blad
		3/4	2861	351	28	57.19	0.21	e
		4/4	2774	274	4	42.04	6	Post + Accessories Box
	2.863x5.606x2.5m	1/5	2864	315	23	32.68	0.29	e Gutter
		2/5	2825	351	6	68.25	7 0.30	Gutter + Blade
		3/5	2861	351	30	68.22	5	Blade
		4/5	2861	351	4 30	68.22	0.30	Blade
		5/5	2774	274	4	73.16	5	
	4.000x5.606x2.5m	1/6	4001	315	28	46.06	0.21	Post + Accessories Box
		2/6	2825 2861	351	4		6	Gutter
		3/6 4/6	2861	351 351	23	68.22 68.22	0.21	Gutter + Blade
		5/6	2861	351	6	68.22	3	
		6/6	2774	274	34	73.16	0.34	Blade
					6		3	Blade
					30		0.30	Post + Accessories Box Blade
					7		8	Didde
					30		0.30	
					7		8	
					40		0.30	
					3		6	
					23		0.29	

🔶 C	omparis	ons Between 3	8 Ranges	Building System Pvt. Ltd.
Data	Model	PERGO-Y	PERGO-M8	PERGO-T500
	Туре	Flat Blade	Flat Blade	Aerofoil Blade
Blade	Specification	158 x 33 x 1.3mm	190 x 40 x 1.6/1.7mm	202 x 50 x 2.0mm
	Reference			
Post	Specification	120 x 120 x 1.6mm	150 x 150 x 2.0mm	127 x 127 x 2.0mm
	Reference			
Beam & Gutter	Specification	175 x 93 x 1.5mm	200 x 123 x 3.0mm	230 x 39.2 x 2.5mm & 120 x 85 x 2.0mm
	Reference			
Control Rod	Specification	20 x 20 x 2.0mm	20 x 20 x 2.0mm	35 x 8.6 x 2.0mm
	Reference	Square Tube	Square Tube	L Bar
Maximum Dimensions with 4 Posts		Width 3m x Projection 4m	Width 4m x Projection 6m	Width 4.5m x Projection 6n
Surface Treatment		AkzoNobel Brand w/ 7 Yrs Warranty	AkzoNobel Brand w/ 10 Yrs Warrant	Domestic Brand w/ 7 Yrs Warrant
Operation	Motorized	\checkmark	\checkmark	✓
	Manual	×	Available soon	\checkmark
Color (Options	RAL9016 Traffic White, RAL7016 Anthracite Grey	RAL9016 Traffic White, RAL7016 Anthracite Grey, RAL9005 Jet Black	RAL9016 Traffic White, RAL7016 Anthracite Grey
	Brand	HZ	HZ	HZ
Motor	Voltage	110V~220V	110V~220V	110V~220V
Vaterproof Protection Level		IP67	IP67	IP67
Max Sqm For 1 N	Motor Controlling	16 m²	32 m ²	40 m ²



Comparisons Between 3 Ranges



Model Data		PERGO-Y	PERGO-M8	PERGO-T500	
Remote Control		Radio Frequency	Radio Frequency	Radio Frequency	
	Freestanding	\checkmark	\checkmark	\checkmark	
Design Configuration	Freestanding & Wall mounted	\checkmark	\checkmark	\checkmark	
	Fit into Existing Structure	×	×	\checkmark	
Beam For Fan		×	\checkmark	\checkmark	
LED Strip Light (standard supply)	Color	Single Warm / Cold White Light	Dual Colours: White and Yellow, Dimmable	3000K Warm White 6000K Cold White	
	Position	Outer Gutter Perimeter	Louver Blade	Louver Blade	
RGB Light Strip or Blue Light Strip or Single Warm White light Strip	Adds-on	RGBW	×	RGB Light Strip	
	Position	Outer Gutter Perimeter	×	Louver Blade	
Wind Resistant (estimated)		150km/h	160km/h ~ 210km/h	160km/h ~ 200km/h	
Snow Loading (estimated)		30cm~50cm THK	36cm~80cm THK	40cm-60cm THK	
Warranty (Electrical Components)		3 Yrs	3 Yrs	3 Yrs	
Limits and Acceptance on the Sizes		Accept only standard sizes from the catalogue	Accept standard sizes and bespoke sizes in between the standard ones	No limits, any bespoke sizes are workable	





Contact Us:

Corporate Office:

C 130, Antop Hill Warehousing Co. Ltd. VIT College Road, Wadala (E), Mumbai – 400037 O: +91 22 20840147

Contact Person:

Vinay Kumar Director – Citadel M: +91 9819234618 E: vinaykumarecitadelinfraas.com



